

## South House 'Underlay' Grade Chinese Plywood

### GENERAL DESCRIPTION:

Core veneers are manufactured from poplar or Eucalyptus grown in China. Surface veneers are usually imported red hardwood, 0.3mm thick prior to sanding. The board is normally manufactured with an odd number of plies, each ply being oriented at 90 degrees to the adjacent one, to create a balanced construction. The central veneer in the core of this product is a single piece veneer, to give maximum stability and flatness as a flooring underlay product.

<b>Board Thickness:</b>	Imported in thicknesses of 3.6, 5.5 mm
<b>Standard Size:</b>	2440 x 1220
<b>Bond Class:</b>	EN314-2
<b>Grade Available:</b>	B/BB Underlay grade. Face veneer well sanded

### PHYSICAL DATA:

<b>Density -</b>	540 - 610 kg/m <sup>3</sup>
<b>Moisture Content -</b>	10% +/- 3%
<b>Strength Data -</b>	Not applicable
<b>Tolerances -</b>	To BS EN 315

**Applications:** Carpet and flooring underlay.

### OTHER INFORMATION:

These boards have been tested to meet the basic requirements of the Construction Products Regulation in accordance with EN 13986 and display a CE mark to demonstrate this.

### EUTR COMPLIANCE:

The product uses Eucalyptus for core and verified imported redwood veneers and is therefore assessed by as being negligible risk under EUTR.